

## The TBF-Deliveryprogram

Pyrotechnic equipment & flamethrowers  
(Flamemaster®, Bigflame®, Lycomaster®)

Fireworks & pyrotechnics

Gas fire dishes

Brandpacks®, fire fluids, fire paste & fire gel

Show lasers

Confetti machines

SFX materials

Film blood, effect granulate, film dust & crash glass

Snow machines

Radio-controlled ignition systems & ignition materials

Fountains

Fog and steam generators, fluids,  
CO<sub>2</sub> jets and smoke generators



# FIREWALL®

closed at any length fire wall

exact switching at the push of a bottom

impressive, height adjustable flame effect

TBF-PyroTec GmbH  
Andreas-Meyer-Str. 39  
22113 Hamburg  
Tel.: +49 40 710 014 05  
Fax: +49 40 710 014 09  
E-Mail: [info@tbf-pyrotec.de](mailto:info@tbf-pyrotec.de)  
[www.tbf-pyrotec.de](http://www.tbf-pyrotec.de)

**TBF** pyrotec  
creating special effects

**TBF** pyrotec  
creating special effects

# Firewall

impressive, height adjustable flame effect

dimensions

H 15 cm | W 31 cm | L 200 cm

Weight: 19kg

Power: 230V AC, 330 Watt

low running costs due to the economical propane burner

exact switching at the push of a bottom

safety engineering with flame controlling

closed at any length fire wall

Matt black fire-resistant powder-coated stainless-steel housing for long service life plus attractive design

Firewall TBF PyroTec opens completely new opportunities to design fire.

The components manufactured in 1.5 or 2 m length can be easily ignited either via DMX or a simple to operate control panel. Specially designed burner tubes produce a closed wall of fire up to <1.6 m in height and almost unlimited latitude. The design allows the ignition of up to 10 modules with one controller.

The proper monitoring by an optical flame sensor and the quickly responding immediate interruption of the gas supply in case of a malfunction combined with low-noise high-energy ignition spark are guaranteeing highest security standards.

Firewall is powered by propane gas and is extremely economical in use.

